



Date 10-6-2025
Fire-retardant treated
Solid wood paneling and cladding

Declaration of Performance (Hestus DoP 04)

Reference: 2412-CPR-1063 – in compliance with EU Regulation 305/2011/EU

Product type	Fire-retardant treated solid wood paneling and cladding. EN 14915:2013
Company	Hestus B.V.
Production site	Westervoortsedijk 73, 6827 AV Arnhem, The Netherlands
Notified certification body & AVCP system	Finotrol Oy, Teollisuuskatu 3, FI-50130 Mikkeli, Finland. Notified certification body no: 2412 has performed initial inspection of the manufacturing plant and production control and performs continuous surveillance, assessment and evaluation of factory production control under system 1 and issued the certificate of conformity of factory production control: Hestus-2412-CPR-1063
Declared performances	In accordance with EN 14915:2013 with reference to Certificate of Performance 2412-CPR-1063

Intended use and mounting

- **Option 1:** Fixed mechanically to substrate. Substrate: Any substrate of classes A1 or A2-s1,d0, ≥ 12 mm thickness, density ≥ 525 kg/m³. With or a ventilated or non-ventilated airgap between product and substrate or with no airgap. Mounting: Profiles horizontally or vertically, horizontal and vertical joints. Nominal thickness >42 mm = B-s2,d0.
- **Option 2:** Fibre-cement flat sheet A2-s1,d0 at least 4,5 mm thickness and density equal to or greater than 1300 kg/m³ (Swisspearl or a similar product). Test reference for option 2: Classification K52-2024 and K53-2024 / MeKA.

Date 10-6-2025

Fire-retardant treated

Solid wood paneling and cladding

Specie	Nominal density range (kg/m ³)	Thickness (mm)	Average dry-uptake (kg/m ³)	Reaction to fire (Euroclass)	Thermal conduct (W/m ² *K) (EN14915/5.6/table 4)
Spruce (Picea Abies)	350-494	15-50	38	B-s1,d0	0,09-0,13
Cedar (Western red cedar)	316-494	15-50	38	B-s1,d0	0,09-0,13
Douglas Fir (Pseudotsuga menziesii)	480-580	15-50	29,1	B-s1,d0	0,11-0,13
Larch (Larix decidua)	550-630	15-50	38	B-s1,d0	0,13-0,18
Larch (Larix decidua)	650-750	15-50	38	B-s1,d0	0,15-0,24
Thermo Spruce (Picea Abies)	330-530	15-50	52,4	B-s2,d0	0,09-0,11
Thermo Spruce (Picea Abies)	310-500	18	39,6	B-s1,d0	0,09-0,11
Thermo Pine (Pinus Radiata)	360-550	15-50	50,4	B-s1,d0	0,09-0,13
Thermo Frake (Terminalia superba)	410-730	15-50	51,4	B-s1,d0	0,13-0,15
Thermo Ayous (Ayous Sterculiaceae)	270-375	15-50	50,4	B-s1,d0	0,09-0,11
Thermo Poplar (genus Populus species)	330-500	15-50	51,4	B-s1,d0	0,09-0,11
Thermo Ash (Fraxinus sp.)	590-680	15-50	41,4	B-s1,d0	0,13-0,18
Intended use and mounting	Option 1 or option 2				
Accoya (Pinus Radiata)	400-600	19	76,2	B-s2,d0	0,13-0,15
Intended use and mounting	Fixed mechanically to substrate. Substrate: Any substrate of classes A1 or A2-s1,d0, ≥t 12mm thickness, density ≥ 525 kg/m ³ . With or a ventilated or non-ventilated airgap between product and substrate or with no airgap. Mounting: Profiles horizontally, horizontal and vertical joints. Nominal thickness >19 mm= B-s2,d0.				

Date 10-6-2025
Fire-retardant treated
Solid wood paneling and cladding

Additional information	
Sound absorption (Hz)	250 Hz – 500 Hz: 0,1 / 1000 Hz – 2000 Hz: 0,3 (EN 14915/ 5.5/ Table 3)
Product structure	Products can be used solid, fingerjointed (only water & boiledproof glue).
Fire retardant solution	Burnblock
Formaldehyde	E1
Pentachlorophenol	0 ppm
Water vapour permeability g (μ)	Density kg/m ³ 450-700: Wet 20-50 / Dry: 50-200 (EN 14915/5.4/table 2)
EU Reach Regulation	Burnblock fire retardant do not contain any kind of chemicals or dangerous substances. Please see specifications: www.burnblock.com

The performances of the products described above are consistent with the declared performance.

This declaration of performance is following the EU regulation 305/2011 on the sole responsibility of the manufacture mentioned above.

Signed on behalf of producer, 10-6-2025



Nienke de Pijper, Hestus